



120 Valley Court
Oak Ridge, TN 37830
Ph: 865-482-5717
FAX: 865-482-1281
zypcoatings.com

Boron Nitride Releasecoat®-PM

Fully-Loaded Boron Nitride Paint/Paste For Permanent Mold or Low Pressure Casting

BN Releasecoat-PM is a “concentrate” that is fully-loaded with Boron Nitride. PM provides a thick, dilutable paint/paste, such that it can be made to almost any consistency or viscosity by merely adding water. PM concentrate saves on shipping costs. Typical dilution is 2 parts water to 1 part concentrate. When diluted PM is a relatively-soft, washcoat-type of coating. BN Releasecoat-PM provides excellent nonwetting and release with aluminum, magnesium, zinc and other nonferrous metals and alloys.

Key Attributes

- Perfect for top-coating over thermal insulating coatings.
- Provides “cosmetic”/mirror-like surface finish with excellent mold release
- Ideal for low-draft, high-drag regions for wheel casting
- Easily applied by air spraying on to hot or cold molds
- Safe, water-based

Ideal Use

- Permanent Molds
- Low Pressure or Gravity Die casting

Use Notes

1. Resuspend if needed. Dilute with water to desired consistency & viscosity .
2. Clean surfaces to be painted of any oils dirt, scale, etc.
3. Apply 1-3 layers by brush or spray like ordinary house paint, drying after each layer
4. Allow to dry thoroughly before use.

Safety Information

- Consult SDS before use.
- Avoid breathing of spray/vapors.
- For Industrial Use only.



Specifications

Active Ingredient	BN
Max Use Temperature	Air 1832 F / 1000 C Vac 2552 F / 1400 C Inert 3272 F / 1800 C
Use Atmosphere	All
Fired Composition	>85% BN
Liquid Carrier	Water
Binder Phase	Magnesium Silicate
Active Ingredient Level	Fully Loaded
Brookfield Viscosity (cps)	22,000-37,000 @4/12
Specific Gravity	1.1
Color	White
Shelf Life (months)	>12
Coverage (ft ² /gal)	100 to 400
Coating pH	7-8
H F R Ratings	1-0-0
Substrate Use	All

Sizes and colors

BN Releasecoat-PM is a white colored paint/paste.

Standard Size: wide-mouth 1 gallon pail.

CAUTION: DO NOT CONTACT WET COATINGS WITH MOLTEN METAL.

ZYP Coatings, Inc. (ZYP) makes no warranties, express or implied, including the warranty of merchantability or fitness for a particular service. Product is for industrial/commercial use only. Users should determine suitability for their use.

In no event will ZYP be liable for any direct, indirect, incidental, special or consequential damages or losses including, but not limited to loss of profits, in any way related to this product regardless of the legal theory asserted. Teflon® - reg. trademark of DuPont.