



120 Valley Court  
Oak Ridge, TN 37830  
Ph: 865-482-5717  
FAX: 865-482-1281  
zypcoatings.com

# Boron Nitride Lubriccoat® Boron Nitride Lubriccoat-Blue®

## Our Best, All-purpose, Coating Concentrate

BN Lubriccoat is our proven “workhorse” release agent for high-temperature use. BN Lubriccoat® is ideal for providing true Teflon®-like non-wetting for all liquid metal transfer system components. Also, BN Lubriccoat is non-reactive and non-stick with glass, slags, fluxes. As a lubricant/non-stick agent, BN Lubriccoat is ideal for hot-pressing and glass forming.

### Key Attributes

- Totally Non-Wetted by Molten Aluminum, Magnesium, Zinc and Their Drosses
- Acts Like Teflon® to Molten Metal
- Protects Ceramics, Metals and Graphite
- Maintenance is Reduced and Operator Satisfaction Maximized
- Applied Like House paint

### Ideal Use

- Launderers & Runners
- Auto-Pour Ladles
- Troughs & Tubes
- Funnels & Spouts
- Filter Bowls, Boxes
- Caster Tips
- Dross Press Heads
- Braze Stop-Off
- Weld Spatter Release

### Use Notes

1. Resuspend if needed. Can dilute with water.
2. Clean surfaces to be painted of any oils dirt, scale, etc.
3. Apply one thin layer by brush, dip or spray like ordinary house paint
4. Allow to dry thoroughly before use.

### Safety Information

- Consult SDS before use.
- Avoid breathing of spray/vapors.
- For Industrial Use only.



### Specifications

Active Ingredient	BN
Max Use Temperature	Air 1832 F / 1000 C Vac 2552 F / 1400 C Inert 3272 F / 1800 C
Use Atmosphere	All
Fired Composition	>85% BN
Liquid Carrier	Water
Binder Phase	Al <sub>2</sub> O <sub>3</sub>
Active Ingredient Level	Fully Loaded
Brookfield Viscosity (cps)	900-1150 @3/60
Specific Gravity	1.2
Color	White, except when specified blue
Shelf Life (months)	>12
Coverage (ft <sup>2</sup> /gal)	100 to 400
Coating pH	2-4
H F R Ratings	1-0-0
Substrate Use	All

### Sizes and colors

Boron Nitride Lubriccoat is a white colored paint. Boron Nitride Lubriccoat-Blue is a blue colored paint that may offer better visibility. We also offer a white paste for uses where a thicker version of our Boron Nitride Lubriccoat is needed: BN Lubriccoat Paste.

Standard Size: wide-mouth 1 gallon pail.  
Also available in 5 gallon pail upon request.

### CAUTION: DO NOT CONTACT WET COATINGS WITH MOLTEN METAL.

ZYP Coatings, Inc. (ZYP) makes no warranties, express or implied, including the warranty of merchantability or fitness for a particular service. Product is for industrial/commercial use only. Users should determine suitability for their use.

In no event will ZYP be liable for any direct, indirect, incidental, special or consequential damages or losses including, but not limited to loss of profits, in any way related to this product regardless of the legal theory asserted. Teflon® - reg. trademark of DuPont.