

120 Valley Court Oak Ridge, TN 37830 Ph: 865-482-5717 FAX: 865-482-1281 zypcoatings.com

# Zirconium Oxide Plus Boron Nitride, Providing Thermal Insulation and Mold Release

ZBN Release contains Zirconium Oxide (ZrO<sub>2</sub>) for thermal insulation along with Boron Nitride (BN) for best mold release with permanent mold or low pressure casting. With ZBN Release, only one single coating provides all you need.

ZBN Release is ready-to-use or can be diluted with water if needed.

## **Key Attributes**

- Thermally insulating with mold release
- Provides nonwetting, non-stick, release, lubrication
- Can be used as is or diluted with water as desired
- Water-based, safe and easy-to-clean-up

#### Ideal Use

- Permanent Molds
- Low Pressure or Gravity Die casting

#### **Use Notes**

- 1. Resuspend if needed. Can dilute with water.
- 2. Clean surfaces to be painted of any oils dirt, scale, etc.
- 3. Apply 1-3 layers by brush or spray like ordinary house paint, drying after each layer.
- 4. Allow to dry thoroughly at room temperature before use.

## **Safety Information**

- Consult SDS before use. 
  Avoid freezing.
- Avoid breathing of spray/vapors.
- For Industrial Use only.



# **Specifications**

NOTE: For enhanced release, blend with BN Releasecoat or BN Type M at around 50% by weight.

## Sizes and colors

ZBN Release is a blue colored paint.

Standard Size: 1 gallon or 5 gallon pail

#### CAUTION: DO NOT CONTACT WET COATINGS WITH MOLTEN METAL.

ZYP Coatings, Inc. (ZYP) makes no warranties, express or implied, including the warranty of merchantability or fitness for a particular service. Product is for industrial/commercial use only. Users should determine suitability for their use. In no event will ZYP be liable for any direct, indirect, incidental, special or consequential damages or losses including, but not limited to loss of profits, in any way related to this product regardless of the legal theory asserted.