

120 Valley Court Oak Ridge, TN 37830 Ph: 865-482-5717 FAX: 865-482-1281 zypcoatings.com

# **Boron Nitride Aerosol Lubricoat®**

# **Convenient Aerosol-Can of Boron Nitride (BN)**

BN Aerosol Lubricoat® is a convenient aerosol can for applying thin, uniform, quick-drying layers of BN onto most any substrate. The aerosol can allows the creation of a dry-film-lubricant and provides the great properties of BN in an easy-to-use/test manner – low electrical conduction; high thermal conduction (like stainless); prevent reactions/interactions between materials; superior release/nonwetting.

# **Key Attributes**

#### Anti-stick:

- · Molten Al, Mg, & Zn
- Hot-Pressing
- Glass Forming
- Weld Spatter
- Braze Stop-Off

## **High-temperature Lubrication:**

- Extrusion
- Superplastic Forming
- Stops galling
- Dry-Film Lubricant (DFL)

### **Ideal Use**

- Reducing Friction
- Providing Release
- Barrier Layer

### **Use Notes**

- 1. Clean surfaces to be painted of any oils dirt, scale, etc.
- 2. Shake can until mixing ball is heard & for 1 minute more
- 3. Hold can 6 to 12 inches from surface & apply thin/uniform coating using even movements
- 4. Allow to dry for 1 to 2 minutes and respray as needed

# **Safety Information**

- · Consult SDS before use.
- Avoid breathing of spray/vapors.
- For indrustrial use only



# **Specifications**

	Active Ingredient		BN
	Max Use Temperature	Air 1832	F / 1000 C
	•	Vac 2552	F / 1400 C
		Inert 3272	F / 1800 C
	Use Atmosphere		All
	Fired Composition (Air	@700 C)	97% BN
	Liquid Carrier Et	thyl Alcoho	I/Acetone
	Gas Propellant	Propar	ne/Butane
	Binder Phase	Magnesiu	m Silicate
	Color		White
	Shelf Life (months		>12
	Coverage (ft²/aerosol-	can)	30-50
	H F R Ratings		2-4-0
	Substrate Use		All
	Other: Nearly water insoluble after dryin		
Can be used at cryogenic temperature			peratures

### Sizes and colors

Product is white:

will gray out on first heat up to 700 C due to small amount of organic binder

Standard Size: 13oz. (369 grams) can Can be purchased as bulk paint with the same formula: BN Aerosol Brushable.

### CAUTION: DO NOT CONTACT WET COATINGS WITH MOLTEN METAL.

ZYP Coatings, Inc. (ZYP) makes no warranties, express or implied, including the warranty of merchantability or fitness for a particular service. Product is for industrial/commercial use only. Users should determine suitability for their use. In no event will ZYP be liable for any direct, indirect, incidental, special or consequential damages or losses including, but not limited to loss of profits, in any way related to this product regardless of the legal theory asserted.