



120 Valley Court
 Oak Ridge, TN 37830
 Ph: 865-482-5717
 FAX: 865-482-1281
 zypcoatings.com

BNSL Binder

Solvent-based Binder Liquid For Creating Your Own Paint

BNSL Binder is one of our most versatile suspension agent/binder liquids. With an alcohol-acetone based vehicle, it is the binder for our mainline aerosol sprays. The binder also has a medium ability to suspend solids and generally produces low to medium viscosity coatings with most refractory powders. With its non-aqueous binder liquid, BNSL not very reactive to materials. Most any powder can be used with it. It has a long shelf life and flash point of 15 F. BNSL Binder is often a preferred binder for first trials due to its utility in air environments and inertness to most powder additives.

Key Attributes

- Moderate water-resistance on ambient drying
- Moderate suspendability of 'filler' powders
- Forms moderate-hardness coatings
- Good in all atmospheres, including air
- Minimal outgassing (H₂O, CO_x)—mostly complete by 150 C
- Dilutable with Ethanol for slower drying or Acetone for faster drying or any combination of these
- Safe, easy-to-use
- No cure needed

Ideal Uses

- Binder/Suspender
- Infiltrant

Possible Fillers

- Compatible with most everything
- Ideal for water-sensitive/reactive materials
- Consider eutectics that form low-melting situations

Use Notes

1. Add refractory 'filler' (<10 microns preferred)
2. Start at 50wt.% powder. Mix by rolling/shaking.
3. If too thick, add ethanol; if too thin, add powder.
4. Re-mix by rolling or shaking.

After making paint above, clean substrate, apply paint, dry (with no cure needed), and place into use.



Specifications

Active Ingredients	>99% MgO-SiO ₂
Max Use Temperature	1600 C
Use Atmosphere	All
Fired Composition/Binder Phase	Glassy Carbon/ Magnesium Silicate
Hardness	Moderate
Liquid Carrier	Ethanol/Acetone
Water Resistance	Moderate
Ability to Suspend Solids	Moderate
Brookfield Viscosity (cps)	185 @2/60
Specific Gravity	0.82
Shelf Life (months)	>12
Coating pH	Not applicable
H F R Ratings	1-3-0
Substrate Use	All
% Volatiles	97

Safety Information

- Consult SDS before use.
- Avoid breathing of spray/vapors.
- For Industrial Use only.

Sizes and colors

BNSL Binder is a cloudy liquid.
 Standard Size: 1 gallon Nalgene container.

CAUTION: DO NOT CONTACT WET COATINGS WITH MOLTEN METAL.

ZYP Coatings, Inc. (ZYP) makes no warranties, express or implied, including the warranty of merchantability or fitness for a particular service. Product is for industrial/commercial use only. Users should determine suitability for their use. In no event will ZYP be liable for any direct, indirect, incidental, special or consequential damages or losses including, but not limited to loss of profits, in any way related to this product regardless of the legal theory asserted.