



120 Valley Court  
 Oak Ridge, TN 37830  
 Ph: 865-482-5717  
 FAX: 865-482-1281  
 zypcoatings.com

# Clearcoat Protectant

## Solvent-based Coating For Preventing Tarnishing

Clearcoat Protectant is an easy-to-apply, solvent-based coating designed to prevent tarnishing of a metal surface. Once applied and dried, the coated area is protected, reducing any corrosion that forms discoloration/dulling of the luster on metals.

Clearcoat Protectant can also be used on non-metallic substrates and even plastic if so desired. Additionally, this product can be used as a thinner for ChillOff or ChemStop coatings.

### Key Attributes

- Provides a clear, tough sealant coating
- Protects from unwanted/ugly tarnishing for metals
- Prevents having to regularly clean metals with special polishes
- Safe solvent-based thinner for ChillOff and ChemStop coatings
- Easy-to-use: applies like house paint by brushing or dipping

### Ideal Use

- Metal surfaces
- Metal flashing
- Metal plaques, signs, and markers
- Ceramics, plastics, organic/wood sealant
- Conservatory liquid for protecting artifacts from environmental deterioration

### Use Notes

1. Clean surfaces to be painted of any oils, dirt, scale, etc.
2. Apply one layer by brush. Apply other layers if needed—drying after prior layer(s). Dipping is also OK.
3. Allow to completely dry at room temperature – takes about ½ hour
4. Clearcoat Protectant can removed with solvents such as Methyleneketone (MEK), Mineral Spirits, Turpentine.



### Specifications

Active Ingredients	Polymer
Max Use Temperature	392 F / 200 C
Use Atmosphere	All
Liquid Carrier	Propionate solvents
Brookfield Viscosity (cps)	8@2/60
Specific Gravity	0.88
Color	Clear to slightly hazy (dries clear)
Shelf Life (months)	>12
Coverage (ft <sup>2</sup> /gallon)	200-400
H F R Ratings	1-3-0
Substrate Use	Any metals which tarnish (Copper, Brass, Bronze, Silver) or need thin protective film (Mild Steel, Aluminum, Stainless) Non-metallics like ceramics/wood/plastic.

### Sizes and colors

Product is clear  
 Standard Size: 8 oz., 32 oz. (quart), 1 gallon  
 Nalgene container

### Safety Information

- Consult SDS before use.
- If heated, avoid breathing of vapors.
- For Industrial Use only.

### CAUTION: DO NOT CONTACT WET SURFACES WITH MOLTEN METAL.

ZYP Coatings, Inc. (ZYP) makes no warranties, express or implied, including the warranty of merchantability or fitness for a particular service. Product is for industrial/commercial use only. Users should determine suitability for their use. In no event will ZYP be liable for any direct, indirect, incidental, special or consequential damages or losses including, but not limited to loss of profits, in any way related to this product regardless of the legal theory asserted.