

120 Valley Court Oak Ridge, TN 37830 Ph: 865-482-5717 FAX: 865-482-1281 zypcoatings.com

Highest Purity Zirconium Oxide (ZrO₂) Coating

Type Z is a relatively-soft, washcoat-type of Zirconium Oxide (ZrO₂) coating that provides high-purity 4% CaO stabilized ZrO₂ which is usable in vacuum and inert atmospheres to 2000 C (3632 F). This coating should NOT be used in air atmospheres.

Key Attributes

- Provides, in a water-based paint, the properties of ZrO₂ lowest thermal conductivty; good high-temperature stability with molten metals, glasses, slags, and salts; inert barrier for reactions, diffusion bonding, brazing etc.
- Applies like housepaint (brush, dip, air-spray)
- Easily applied by air spraying on to hot or cold graphite crucibles and molds
- Good with highly reactive molten metals
- Safe, Water-Based

Ideal Use

- Graphite crucibles and molds
- Anti-stick with diffusion bonding

Use Notes

- 1. Resuspend if needed. Can dilute with water or with YZ Binder/Thinner if desired.
- 2. Clean surfaces to be painted of any oils dirt, scale, etc.
- 3. Apply 1-3 layers by brush, dip or air-spray like ordinary house paint, drying after each layer
- 4. Allow to dry thoroughly at room temperature before use.

Safety Information

- Consult SDS before use.
- Avoid breathing of spray/vapors.
- For Industrial Use only.



Specifications

| Active Ingredient Max Use Temperature | ZrO_2^* (CSZ) |
|--|---------------------|
| • | C) 3632 F / 2000 C |
| , | nt) 2732 F / 1500 C |
| • | TRECOMMENDED |
| Use Atmosphere | Vacuum or Inert |
| • | |
| Fired Composition | >99% CSZ |
| Liquid Carrier | Water |
| Binder Phase | Cellulosic |
| Brookfield Viscosity (cps |) 2500 @4/60 |
| Specific Gravity | 2.17 |
| Color | Cream |
| Shelf Life (months | >12 |
| Coverage (ft²/gal) | 100 to 400 |
| Coating pH | 7-8 |
| H F R Ratings | 1-0-0 |
| Substrate Use | All |
| * with 4 wt% CaO stabilizer | |

Sizes and colors

Type Z is a cream colored paint.

Standard Size: 1 gallon Nalgene container

CAUTION: DO NOT CONTACT WET COATINGS WITH MOLTEN METAL

ZYP Coatings, Inc. (ZYP) makes no warranties, express or implied, including the warranty of merchantability or fitness for a particular service. Product is for industrial/commecial use only. Users should determine suitability for their use. In no event will ZYP be liable for any direct, indirect, incidental, special or consequential damages or losses including, but not limited to loss of profits, in any way related to this product regardless of the legal theory asserted.