

120 Valley Court Oak Ridge, TN 37830 Ph: 865-482-5717 FAX: 865-482-1281 zypcoatings.com

# **Zypcoat® BAS**

# **Very-High-Temperature Coating that forms CELSIAN In-situ**

Zypcoat® BAS is a water-based coating of Barium Carbonate (BaCO<sub>3</sub>), Aluminum Oxide (Al<sub>2</sub>O<sub>3</sub>), and Silicon Oxide (SiO<sub>2</sub>). The coating forms Celsian (BaAl<sub>2</sub>Si<sub>2</sub>O<sub>8</sub>) above 1000 C. Celsian has high chemical stability and reportedly melts circa 1760 C. Zypcoat BAS is a very economical coating that is usable to at least 1650 C on most all substrates and with all atmospheres. Thus, Zypcoat BAS should be applicable as a protective layer for most refractories.

# **Key Attributes**

- Provides non-reactivity with many materials, including molten Aluminum
- Use temperature expected to be at least 1650 C in all atmospheres
- Erosion-resistant/tough coating on all substrates
- Very economical, water-based, easy-to-use and cleanup

#### **Ideal Use**

- Very-high-temperature use areas
- Stopping reactions/interactions with other refractory substrates
- Barrier coating to prevent diffusion, reactions, and sticking of parts during heat treating

#### **Use Notes**

- 1. Resuspend if needed.
- 2. Use full strength, or dilute as desired.
- 3. Clean surfaces to be painted of any oils, dirt, scale, etc.
- 4. Apply a thin layer by brush.
- 5. Allow to thoroughly dry before use.

### Safety Information

- Consult SDS before use.
- Avoid breathing of spray/vapors.
- For Industrial Use only.



## **Specifications**

**Active Ingredient**  $BaCO_3 - Al_2O_3 - SiO_2$ Max Use Temperature with All Atmospheres >=1650 C (>= 3002 F)Major = Celsian, BaAl<sub>2</sub>Si<sub>2</sub>O<sub>8</sub> Fired Composition **Liquid Carrier** Water Binder Phase **Proprietary** Brookfield Viscosity (cps) 100 @ 2/60 Specific Gravity Color Yellow-Orange Shelf Life (months) >12 100-400 Coverage (ft<sup>2</sup>/gal) Coating pH 7-8 H F R Ratings 1-0-0 Substrate Use ΑII

#### Sizes and colors

Zypcoat BAS is a yellow-orange colored paint. Standard size: 1 gallon pail

#### CAUTION: DO NOT CONTACT WET COATINGS WITH MOLTEN METAL.

ZYP Coatings, Inc. (ZYP) makes no warranties, express or implied, including the warranty of merchantability or fitness for a particular service. Product is for industrial/commercial use only. Users should determine suitability for their use. In no event will ZYP be liable for any direct, indirect, incidental, special or consequential damages or losses including, but not limited to loss of profits, in any way related to this product regardless of the legal theory asserted.