



120 Valley Court  
 Oak Ridge, TN 37830  
 Ph: 865-482-5717  
 FAX: 865-482-1281  
 zypcoatings.com

**Chilloff**

## Boron Nitride Solvent-Based Polymer Coating

Chilloff is a gray-colored, solvent-based coating that is adherent to all substrates and dries to form a tough permanent BN coating to dissipate heat quickly.

### Key Attributes

- Easy to use on metals, plastics, and other surfaces
- Permanent coating, insoluble in alcohols, acetone and water
- Solutionized polymer gives toughness to dried coating
- Smooth, uniform layers to cool/chill down surfaces

### Ideal Uses

- Dissipating heat derived from electronics
- To provide a smooth, lubricating surface

### Use Notes

1. Resuspend if needed.
2. Clean surface to be painted of any oils, dirt, scale, etc.
3. Apply coating like housepaint (bristle brush or dipping).
4. Allow to thoroughly dry, typically less than an hour at room temperature.
5. Ready to use after drying.

### Safety Information

- Consult SDS before use.
- Avoid breathing of vapors.
- For Industrial use only.



### Specifications

Active Ingredients	BN
Max Use Temperature	250 C (450 F)
Use Atmosphere	All
Liquid Carrier	Solvent Mixture
Brookfield Viscosity (cps)	~2000@4/60
Specific Gravity	0.9
Color	Gray
Shelf Life (months)	>12
Coverage (ft <sup>2</sup> /gal.)	100-400
H F R Ratings	1-2-0
Substrate Use	Metals, plastics, ceramics

Clean up with MEK or mineral spirits.

### Sizes and colors

Product is gray  
 Standard Sizes: 8 oz. (237 ml) container

ZYP Coatings, Inc. (ZYP) makes no warranties, express or implied, including the warranty of merchantability or fitness for a particular service. Product is for industrial/commercial use only. Users should determine suitability for their use. In no event will ZYP be liable for any direct, indirect, incidental, special or consequential damages or losses including, but not limited to loss of profits, in any way related to this product regardless of the legal theory asserted.